

5M OPEN END EXTENDER

RATED CURRENT	32A
RATED VOLTAGE	250V
RATED IMPULSE VOLTAGE	4kV
POLLUTION DEGREE	2
MECHANICAL CODING	Code 1
LOCKABLE	Yes
COLOR OF CODING/ CONTACT CARRIER	Blue
MARKING OF POLES	L, N, PE
COLOR OF HOUSING INCLUSIVE STRAIN RELIEF	Black
MODEL	Extension cable
INNER CORES	Single cores LSOH
SINGLE CORES	H07Z-R
COLOUR OF CODING PIN	Sky blue (C1)
NOMINAL CROSS SECTION CONDUCTOR	6mm ²
DEGREE OF PROTECTION (IP)	IP20
WIRE STRIP LENGTH	10mm
SHEATH STRIP LENGTH	200mm
PREPARATION OF CONDUCTOR ENDS	Tin-plated
CABLE DIAMETER MIN.	-
VERSION OF CABLE	Female - Male

TYPE OF CORD SET	Connecting Cable
VERSION CABLE END 1	Open
VERSION CABLE END 2	Male
DIMENSIONS	Total length - 5M (Not including open end)
CLASSIFICATIONS	ECLASS 11 ECLASS 8.1 27440604 ETIM 8.0 EC002587 ETIM 7.0 EC002587 ETIM 6.0 EC002587 ETIM 5.0 EC002587 ETIM 4.0 EC002587

